



Boom Deployment Drill December 11, 2018

Emergency Action Plan - Oil Release to Waters of the State

Dickerson Generating Station 21200 Martinsburg Road Dickerson Maryland 20842



Dickerson Generating Station




Three coal-fired steam units:

Unit 1 - 179 MW (net), 1959 Unit 2 - 179 MW (net), 1960 Unit 3 - 179 MW (net), 1962 Two Gas/Oil-fired GE 7F CTs

H1 CT - 147/167 MW (net), 1992 H2 CT - 147/167 MW (net), 1993 One Oil-fired Blackstart CT D1 CT - 18 MW (net), 1967 Dickerson Sta.

Whites Ferry

Water Intakes



OP TO PROPERTY OF THE PARTY OF

USCG PREP Guidelines

Purpose

The National Preparedness for Response Exercise Program (PREP) was developed to demonstrate the intent of sections of Federal Regulations under:

- Oil Pollution Act of 1990 (OPA 90),
- Federal Water Pollution Control Act (FWPCA),
- Spill response preparedness [33 U.S.C. 1321 (j)]

The PREP satisfies the exercise requirements of:


- US Coast Guard,
- Environmental Protection Agency (EPA),
- Research and Special Programs Administration (RSPA) Office of Pipeline Safety, and
- Minerals Management Service (MMS).



Planning Volumes for Oil:

Maximum Most Probable (USCG) / Medium (EPA) Discharge:

- For EPA-regulated facilities, a discharge greater than 2,100 gallons
 [50 barrels] and less than or equal to 36,000 gallons [858 barrels] or
 10 percent of the capacity of the largest tank at the facility,
 whichever is less [40 CFR 112.20].
- Dickerson largest oil tank is 10,000,000 * 10% = 1,000,000 gallons



OP THE PROPERTY OF THE PROPERT

Equipment Deployment Exercises

The requirements for the equipment deployment exercise are:

- Personnel that would normally operate or supervise the operation of the response equipment must participate in the exercise.
- Response equipment must be in good operating condition.

Dickerson has a trailer containing 1200' of river boom to deploy at Whites Ferry as the primary means of mitigating a release to the river.



Successful Completion of Government-Initiated Unannounced Exercise Val

The objectives in a government-initiated unannounced exercise for likely discharge include the following:

- Conducting proper notifications;
- Arrival of containment boom as specified in the approved response plan within one hour of detection of the discharge and the subsequent successful deployment;
- Arrival of oil recovery devices as specified in the approved response plan within two hours of detection of the discharge and the subsequent successful operation/simulated recovery;

Boom is to be on the water within 1 hr. and vac truck arrival within 2 hrs.


Dickerson Equipment Deployment Drill December 11, 2018



First a safety meeting.....



Dickerson Equipment Deployment Drill December 11, 2018








Dickerson Equipment Deployment Drill December 11, 2018



Backing boom trailer into position on boat ramp



Dickerson Equipment Deployment Drill December 11, 2018





Unload all boom rather than flake from trailer. If not, any snag may drag trailer into water once ferry begins to pull boom across river.

Dickerson Equipment Deployment Drill December 11, 2018





Take one end to MD anchor point near water's edge.

Dickerson Equipment Deployment Drill December 11, 2018





Next, bring VA end closest to boat, leaving enough slack to load extra to pull from secured anchor on boat to VA side land anchor.

Dickerson Equipment Deployment Drill December 11, 2018





Ensure no cross overs; cables on top and bottom of boom must remain parallel and not twist once in water.

Dickerson Equipment Deployment Drill December 11, 2018






Chain used to connect boom cable to anchoring points. A come-along used to release boom from boat anchor point, once secured to VA shore anchor.

Dickerson Equipment Deployment Drill December 11, 2018





Loading slack onto ferry deck, and then secure to back of boat. Potential snag with ferry drive mechanism if secured to front of boat.

Dickerson Equipment Deployment Drill December 11, 2018



Chase boat added as precaution to runaway boom or ferry...



Dickerson Equipment Deployment Drill December 11, 2018






Ferry at VA side of river; unable to get boom to VA anchor point. Weight of ferry and water against boom caused concern for ferry cable break.

Dickerson Equipment Deployment Drill December 11, 2018





Strong river current pushed water over boom at bottom of loop. Oil would not be held with this booming strategy.



Dickerson Equipment Deployment Drill December 11, 2018





(left) Anchor point (MD) pulled out of ground, (right) and barely held for lower cable anchor



Dickerson Equipment Deployment Drill December 11, 2018

Overall a successful deployment drill.

Lessons learned:

A full river crossing is difficult given the strain on a single 1200' line of boom.


Different boom strategies to be employed based on river currents, as indicated by river height. Ferry operator wants < 4' average for the 3 closest USGS gauges - Point of Rocks, Edwards Ferry & Little Falls..

On Dec. 11th they were:

Point of Rocks 4'
Edwards Ferry 6.5'
Little Falls 1.1'
AVG 3.9'

Dickerson Equipment Deployment Drill December 11, 2018

<u>Lessons learned</u>: Alternative booming strategies







Dickerson Equipment Deployment Drill December 11, 2018

Lessons learned:

Use Mason Island to funnel oil and contain on narrow side of river.





Cenon Dickerson NPDES Permit Renewal Effective 9/01/2018



Twice daily visual check at outfall for contaminants

47 6053931 01/28/2019 I Peyton 08:20 EST

LOG ENTRY SHARED FROM 'DCK Steam Plant and FGD' by ui1148a on 1/28/2019 08:21 EST

Category: Environmental

Data: Spill Checks Complete: YES; Station: Outside Operator; Checked Outfall 001 for visible sheen: YES Use Outfall 001 sampling platform as the standard point for observation; Visible Sheen Present?: NO 8 hours after last observation; Contaminants Present?: NO

Spill Checks Completed

6054285 01/28/2019 22:15 FST B Dilworth

LOG ENTRY SHARED FROM 'DCK Steam Plant and FGD' by ub4053r on 1/29/2019 00:56 EST

Category: Environmental

Data: Spill Checks Complete: YES; Station: Outside Operator; Checked Outfall 001 for visible sheen: YES Use Outfall 001 sampling platform as the standard point for observation; Visible Sheen Present?: NO 8 hours after last observation; Contaminants Present?: NO

Spill Checks Completed